



ELVALOY™ PTW

Copolymer

Description			
Product Description	ELVALOY™ PTW is an ethylene terpolymer, used as an Impact Modifier for a variety of polymers.		
Restrictions			
Material Status	Commercial: Active		
Typical Characteristics			
Uses	Polymer Modifier		
Characteristics / Benefits	General purpose toughener for a variety of polymers. Promotes toughening of PET.		
Applications	When used in a CPET tray formulation, ELVALOY™ PTW provides both toughening and increases the melt strength of the PET.		
Typical Properties			
Physical	Nominal Values	Test Method(s)	
*Density ()	0.94 g/cm ³	ASTM D792	ISO 1183
*Melt Flow Rate (190°C/2.16kg)	12 g/10 min	ASTM D1238	ISO 1133
Thermal	Nominal Values	Test Method(s)	
*Melting Point (DSC)	72 °C (161.6 °F)	ASTM D3417	ISO 3146
Processing Information			
*Maximum Processing Temperature	310 °C (590 °F)		
General Processing Information	<p>Optimizing Use Level: This material is an ethylene terpolymer that is most effective when it is well dispersed into a polymer. The single screw or twin-screw extrusion equipment used to melt and pump the molten polymer provides the dispersive mixing. Increasing the loading of the ethylene terpolymer in the polymer makes it more difficult to develop the required degree of dispersion. The best improvement in cold temperature impact resistance may occur at an intermediate loading in the case where the extrusion equipment has limited mixing capabilities. On single screw extruders, increasing the screw speed has been found to improve the quality of the dispersion and observed tray toughness.</p> <p>Handling/Storage of Concentrate: ELVALOY™ PTW is supplied in polyethylene bag lined boxes or bags. The product does not require drying but the material should be handled in a way that minimizes moisture pick-up. For example reseal bags or box liners when partial bags or boxes are not being used.</p> <p>Feeding Extruder: The melting point of the ELVALOY™ PTW is 72°C (162°F) so a split feed single screw extrusion feed hopper will be required in cases where the temperature of a hot dried polymer such as PET exceeds the melting point of the ELVALOY™ PTW.</p>		
FDA Status Information	<p>ELVALOY™ PTW Resin Modifier may be used at up to a level of 7 percent in crystallized polyethylene terephthalate (CPET) trays that will hold food for microwave and conventional oven heating. Such use may be properly said to comply fully with the Federal Food, Drug, and Cosmetic Act and all applicable food additive regulations.</p> <p>ELVALOY™ PTW Resin Modifier may be used at up to a level of 3 percent in amorphous polyethylene terephthalate (APET) trays that will hold food under Conditions of Use E and F (room temperature and refrigerated storage with no thermal treatment in the container). Such use may be properly said to comply fully with the Federal Food, Drug, and Cosmetic Act and all applicable food additive regulations.</p>		

The information and certifications provided herein are based on data we believe to be reliable, to the best of our knowledge. The information and certifications apply only to the specific material designated herein as sold by Dow and do not apply to use in any process or in combination with any other material. They are provided at the request of and without charge to our customers. Accordingly, Dow cannot guarantee or warrant such certifications or information and assumes no liability for their use.

Regulatory Information

For information on regulatory compliance outside of the U.S.A., consult your local Dow representative.

Articles made with PET or other thermoplastics modified with small amounts of ELVALOY™ PTW should be tested to confirm they comply with applicable food contact regulations in your region.

Safety & Handling

For information on appropriate Handling & Storage of this polymeric resin, please refer to the material Safety Data Sheet.

A Product Safety Bulletin, material Safety Data Sheet, and/or more detailed information on extrusion processing and/or compounding of this polymeric resin for specific applications are available from your Dow representative.

Product Stewardship

The Dow Chemical Company and its subsidiaries (“Dow”) has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our Product Stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our Product Stewardship program rests with each and every individual involved with Dow products – from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

Customer Notice

Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

Medical Applications Policy

NOTICE REGARDING MEDICAL APPLICATION RESTRICTIONS: Dow will not knowingly sell or sample any product or service (“Product”) into any commercial or developmental application that is intended for:

- a. long-term or permanent contact with internal bodily fluids or tissues. “Long-term” is contact which exceeds 72 continuous hours (or for PELLETHANE™ Polyurethane Elastomers only, which exceeds 30 days);
- b. use in cardiac prosthetic devices regardless of the length of time involved (“cardiac prosthetic devices” include, but are not limited to, pacemaker leads and devices, artificial hearts, heart valves, intra-aortic balloons and control systems, and ventricular bypass-assisted devices);
- c. use as a critical component in medical devices that support or sustain human life; or
- d. use specifically by pregnant women or in applications designed specifically to promote or interfere with human reproduction.

Dow requests that customers considering use of Dow products in medical applications notify Dow so that appropriate assessments may be conducted.

Dow does not endorse or claim suitability of its products for specific medical applications. It is the responsibility of the medical device or pharmaceutical manufacturer to determine that the Dow product is safe, lawful, and technically suitable for the intended use. **DOW MAKES NO WARRANTIES, EXPRESS OR IMPLIED, CONCERNING THE SUITABILITY OF ANY DOW PRODUCT FOR USE IN MEDICAL APPLICATIONS.**

Disclaimer

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, the Customer is responsible for determining whether products and the information in this document are appropriate for the Customer’s use and for ensuring that the Customer’s workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Dow assumes no obligation or liability for the information in this document. **NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**

NOTICE: If products are described as “experimental” or “developmental”: (1) product specifications may not be fully determined; (2) analysis of hazards and caution in handling and use are required; (3) there is greater potential for Dow to change specifications and/or discontinue production; and (4)

although Dow may from time to time provide samples of such products, Dow is not obligated to supply or otherwise commercialize such products for any use or application whatsoever.

Additional Information

North America

U.S. & Canada: 1-800-441-4369
1-989-832-1426
Mexico: +1-800-441-4369

South Africa +800-99-5078

Europe/Middle East

All Countries +31-11567-2626
+800-3694-6367
Italy: +800-783-825

Asia Pacific +800-7776-7776
+60-3-7958-5392

Latin America

Argentina: +54-11-4319-0100
Brazil: +55-11-5188-9000
Colombia: +57-1-219-6000
Mexico: +52-55-5201-4700

<http://www.dow.com>

Published August 2019

© 2019 The Dow Chemical Company

Version: 163.0

Last modified at 8/12/2019 7:41 AM